



Basic Screen 5%

Silent Gliss is proud of its competence in textiles. Our collection offers a wide variety of fabrics for most projects. Our offer has now expanded to include the new Basic Screen 5% – a reliable screen fabric for standard applications at a great price. It is available in four colours, flame retardant and equipped with Oeko-Tex and Greenguard certification.

www.silentgliss.co.uk
www.silentglissglobal.com

Silent Gliss Ltd.
Pyramid Business Park
Poorhole Lane, Broadstairs
Kent CT10 2PT
Great Britain

Tel: +44 (0) 1843 863571
Fax: +44 (0) 1843 864503
info@silentgliss.co.uk

Silent Gliss Global Ltd.
Pyramid Business Park
Poorhole Lane, Broadstairs
Kent CT10 2PT
Great Britain

Tel: +44 (0) 1843 874250
Fax: +44 (0) 1843 874457
info@silentglissglobal.com

SGGB_SGG_L_SG_4907_April_2014



- 1 Exclusive ...
for our contract partners
- 2 First-class ...
functionality with the usual Silent Gliss quality
- 3 Amazing ...
price-performance ratio

© HG Esch

The Roller Blind Silent Gliss 4907



We Optimise – You Benefit

We have worked hard to create a compelling package for the contract market.

By developing the Roller Blind Silent Gliss 4907 and combining it with the new Basic Screen 5% you now have an extremely attractive system solution.



Exclusively developed for our contract partners

- Simple, chic and discreet design for every situation.
- Minimal light gap for optimum lighting conditions.
- Save time and money through quick and easy installation.

First-class functionality with the usual Silent Gliss quality

- Tested with 10,000 test cycles for a very high durability.
- Elegant, rust free chain and strong brackets.

Amazing price

- Fewer parts, limited options – better price.
- Combined with Basic Screen 5%, the Silent Gliss 4907 offers a quality/price ratio that cannot be matched.

Silent Gliss 4907

Technical information

Feature	Silent Gliss 4907
Max. width	1.8m
Min. width	50cm
Max. height	2.8m
Max. m ²	5m ²
Max. weight	2.5kg
Traction	2.0–2.5kg
Tube diameter	32mm
Brackets	Die cast full metal
Bracket colour	White
Bottom bar	Round
End caps	Metal
Chain	4.5mm
Ceiling / wall / recess fitting	Yes



Basic Screen 5%

Characteristics	
Transparency	Semi transparent
Fabric qualities	Stiff
Composition DIN 60 001	30% Polyester, 70% PVC
Weight (g/m ²) DIN EN 12127	410
Thickness (mm) DIN EN ISO 2286-3	0.55
Max. width (cm)	195
Widths in stock (cm)	200
Flame retardant	B1 (DIN 4102-1)
Colour fastness DIN EN ISO 105-B02	5-6
Applicable in humid areas	Yes
Special colours minimum order quantity	5000 m
Green building	This fabric can assist in the achievement of green building ratings

Optical and solar coefficients (DIN EN 410)				
Colour	3001	3015	3006	3007
Visible light transmission (%)	20.3	14.4	8.0	7.2
Visible light reflectance (%)	70.1	48.3	21.8	3.5
Visible light absorption (%)	9.6	37.3	70.2	89.4

Washing instructions	
Rub wet	
Do not tumble dry	
Do not dry-clean	
Do not bleach	
Do not iron	

Processing	
Welding	Yes
Individual design through laser cut	No
Digital printing possible	Yes



For more information please refer to <http://fabrics.silentgliss.com/basicscreen>